GEKA® plus watering showers

GEKA® plus watering shower

Advantage / benefit:	One-hand quick-action valve with KR locking clamp for continuous operation
Material:	Device body: light metal; lever: brass CW617N; GEKA® plus connection: brass CW617N chrome-plated
Area of application:	Fine water dosing enables use for outdoor plants as well as for "market-fresh"

spraying and cleaning of vegetables;

in industry: for dosing and filling (limitedly resistant to chemicals) or for precleaning of devices, machines, vehicles and

installations in the field of agriculture and construction, in industry etc.

Connection female thread mm	24.66	
Connection female thread	G 3/4"	
Connection male thread mm	26.44	
Water throughput at 6 bar I/min	approx. 67	
PU units	1	
Covering box units	20	
Catalogue no.	525SB	
FDV no	51 5250 9	



GEKA® plus watering shower plastic/metal

Advantage / benefit:	Thermally insulating for use with cold and hot water
Material:	. Device body: plastic PP;
	lever and threaded connections: brass CW614N/CW617N;
	GEKA® plus connection: brass CW617N chrome-plated

Connection female thread mm	24.66	
Connection female/male thread	G 3/4"	
Connection male thread mm	26.44	
Water throughput at 6 bar I/min	approx. 67	
PU units	1	
Catalogue no.	525PLSB	
EDV no.	51.5251.9	

GEKA® plus CC watering bar







Spare valve 530KORSB see page 96





Advantage / benefit: Perfect for watering of plants in CC containers, also perfect with very narrow étagères

Material: light metal; GEKA® plus connection: brass CW617N chrome-plated

GEK A® plus quick coupling

ConnectionGENA" plus quick coupling			
Number of nozzle bores	32		
Pipe length cm	65		
PU units	1		
Catalogue no.	5115AKSB		
EDV no.	51.5115.9		

