

CONCRETE PUMPING 85 BAR (1275 PSI) - HEAVY DUTY


TUBE : BLACK CONDUCTIVE NR - ABRASION RESISTANT
REINFORCEMENT : HIGH TENSILE STEEL CORDS
COVER : BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT
APPLICATION : HEAVY DUTY HIGH PRESSURE CONCRETE PLACEMENT AT CASTING SITE.
TEMPERATURE : -30°C +80°C (-22°F +176°F)
BRAND TEXT : ALFAGOMMA -ITALY- T-740 85 BAR (1275 PSI) W.P. HEAVY DUTY CONCRETE PUMPING (omega)
BRAND TYPE : YELLOW LETTERS
NOTE :
APPROVALS :
SAFETY FACTOR : 2:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
740AA0516977N0	51	2	69	9	2160	85	1275		255	61	61
740AA0638577N0	63	2 1/2	85	11	3380	85	1275		265	61	61
740AA0901677N0	90	3 9/16	116	13	5930	85	1275		450		
740AA1022877N0	102	4	128	13	7510	85	1275		510		
740AA1275577N0	127	5	155	14	9800	85	1275		635		
740AA1528677N0	152	6	186	17	13370	85	1275		760		


... pružné partnerství