

GUMEX

// 256AA



Water-irrigation 18 bar (270 psi) - Heavy duty

Tube: black EPDM.

Reinforcement: high tensile textile cords.

Cover: black EPDM - abrasion and ozone resistant.

Application: heavy duty water discharge.

Specially designed for high pressure irrigation systems.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⊙		⊙		⌒		⌘		Ⓜ	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	61,00	2,40	18	270	45	650				1,070	0,72	
60,0	2 3/8"	72,00	2,83	18	270	45	650				1,390	0,94	
70,0	2 3/4"	82,00	3,23	18	270	45	650				1,610	1,09	
76,0	3"	88,00	3,46	18	270	45	650				1,720	1,16	
80,0	3 1/8"	92,00	3,62	18	270	45	650				1,880	1,27	
90,0	3 1/2"	102,00	4,02	18	270	45	650				2,080	1,40	
102,0	4"	114,00	4,49	18	270	45	650				2,360	1,59	
120,0	4 3/4"	132,00	5,20	18	270	45	650				2,870	1,93	
152,0	6"	168,00	6,61	18	270	36	540				4,920	3,31	