

GUMEX

// 185AA



Compressed air 20 bar (300 psi) - Standard duty

Tube: black synthetic elastomer - oil mist resistant.

Reinforcement: high tensile textile cords.

Cover: black synthetic elastomer with longitudinal yellow stripes - abrasion and ozone resistant.

Application: compressed air and general industrial applications.

Constant operation: -10 °C +60 °C (+14 °F +140 °F)

↻		↻		⊙		⊙		⌒		⚡	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	12,00	0,47	20	300	60	900	48,0	1,89		0,120	0,09
8,0	5/16"	14,00	0,55	20	300	60	900	64,0	2,52		0,145	0,10
10,0	3/8"	17,00	0,67	20	300	60	900	80,0	3,15		0,205	0,14
13,0	1/2"	21,00	0,83	20	300	60	900	104,0	4,09		0,280	0,19
16,0	5/8"	24,00	0,94	20	300	60	900	128,0	5,04		0,350	0,24
19,0	3/4"	28,00	1,10	20	300	60	900	152,0	5,98		0,460	0,31
25,0	1"	35,00	1,38	20	300	60	900	200,0	7,87		0,645	0,44