

// ALFACHEM EN 10PG - 5J551 EN B **NEW**



Acid-chemical S&D 10 bar (150 psi) - Standard duty

EN 13765 Type 2

Inner wire: polypropylene coated steel wire.

Tube: polypropylene film.

Cover: grey PVC coated fabric with helicoidal black stripe-blue letters.

Outer wire: galvanised steel wire.

Application: acid and chemical suction and delivery. Specially designed for tank truck applications.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

Electrical conductivity: ensured by the two wires in contact with fittings.

Electrical resistance: ≤ 2,5 Ω/m up to DN 50 mm (2")
≤ 1,0 Ω/m over DN 50 mm (2")

Item Code	Product Code	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)	Length (m)
2016461	5J551ENB025375XHU	25,0	1"	39,0	1,54	10	150	40	600	125	4,92	90,00	0,990	0,67	30,000
2017312	5J551ENB032445XHU	32,0	1 1/4"	44,0	1,73	10	150	40	600	150	5,91	90,00	1,020	0,69	30,000
2017314	5J551ENB040535XHU	40,0	1 9/16"	53,0	2,09	10	150	40	600	150	5,91	90,00	1,510	1,02	30,000
2016463	5J551ENB050645XHU	50,0	2"	64,0	2,52	10	150	40	600	200	7,87	90,00	1,630	1,10	30,000
2017310	5J551ENB065785XHU	65,0	2 9/16"	78,0	3,07	10	150	40	600	200	7,87	90,00	2,450	1,65	30,000
2017286	5J551ENB080945XHU	80,0	3 1/8"	94,0	3,70	10	150	40	600	300	11,81	90,00	3,100	2,09	30,000
2016956	5J551ENB100225XHU	100,0	4"	122,0	4,80	10	150	40	600	400	15,75	90,00	4,960	3,34	30,000